

GLV

Operator Manual



STARLINE®
PROFESSIONAL WASH SYSTEMS



WARNING

Before installation and commissioning, you must read the safety instructions and warnings carefully and all the warning labels attached to the equipment.



IMPORTANT

Failure to comply (even partially) with the instructions given in this manual will invalidate the product warranty and relieves the manufacturer of any responsibility



IMPORTANT

The alteration of machine operation, design or the replacement of parts not approved by the manufacturer may void warranties and approvals.



IMPORTANT

This machine is intended for commercial use only.

CONTENTS

Safety Instructions.....	3
Installation.....	4
Installation Diagram.....	5
Operating Procedures.....	6
Troubleshooting.....	8
Schematic Diagram.....	9
Accessories.....	10

We have checked that the contents of this document correspond to the model described. There may be discrepancies nevertheless, and no guarantee can be given that they are completely identical. The information contained in this document is reviewed regularly and any necessary changes will be included in the next edition. We welcome suggestions for improvement.

Specifications and document subject to change without prior notice.

Information supplied in this manual is copyright. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical without the express permission of the author / publisher.

Service 0800 782 754

Parts 09 829 0930

STARLINE[®]

Manufactured in New Zealand by Washtech Ltd.
414 Rosebank Road, Avondale, Auckland 1026.
PO BOX 90548, Auckland

Safety Instructions



WARNING

Equipment contains dangerous voltages and can be hazardous if installed or operated incorrectly. non-compliance with warnings or failure to follow the instructions contained in this manual can result in loss of life, severe personal injury or serious damage to property.

Installation

- Use qualified, skilled personnel
- Follow installation instructions
- Connect to correct voltage and supply current
- Provide fully accessible electrical Isolation Switch & water supply valves

Training and Supervision

- Read and understand the Operating instructions and train all staff
- This appliance must not be operated by children or infirm persons
- Machine front panel may be removed to access chemical pumps. Access of any further wiring or componentry must only be done by suitably qualified and trained personnel – internal hazards include live electrics and very hot surfaces
- This appliance is not intended for use as a stepladder

Hot Surfaces

- Some surfaces may be hot or very hot

Chemicals

- Commercial dishwashing detergents are hazardous – handle with care
- Read and follow the safety information found on the labels of detergent containers and Material Safety Data Sheets
- Use protective eyewear and clothing if decanting containers

Hot Water

- Do not put hands in wash water which may be over 60°C and contain hazardous caustic detergent
- Rinse water can be over 90°C
- Door safety switches are designed for emergency use only

Cleaning

- Do not hose down the machine or splash water over the exterior
- Watch for broken glass etc when cleaning the inside of the machine

Service/repair

- Under no circumstances the user should attempt to carry out repairs
- All service/repair work must be carried out by qualified personnel only

Power Cord Replacement

- If the supply cord is damaged, it must be replaced by the manufacturer or its service agent or a similar qualified person in order to avoid a hazard

Installation Checklist



WARNING

Installer must be suitably qualified and ensure compliance with all codes and standards including AS/NZS3500.1.

Unpack

- Unpack the machine, check for damage and complete delivery.

Positioning

- Place machine on sound waterproof self draining floor and adjust feet to level
- Allow room for adjacent chemical containers

Water

- Flush supply lines before connection
- Connect hose supplied to adjacent accessible isolator valve – 20 mm 3/4 male
- Flow rate required – 20 litres per minute
- Temperature – 65°C
- Consumption per cycle – 2.6 litres
- Pressure required – 200-350 kPa – fit limiter above this pressure
- Back Flow – Atmospheric Vacuum Breaker fitted
- Potable water quality is required – filter or soften if necessary

Water Quality Requirements

Hardness	fH	dH	ppm	gf/gal	pH		
Min	2	1	220	1	7		
Max	10	6	100	6	8		
Ions	Cl ⁻	SO ₄	Fe	Mn	Cu	Cl ₂	
Max mg/L	100	400	0.1	0.5	0.05	0.1	

Power

- Machine ships single phase 25 A 230V 50Hz

Waste

- Connect drain pump hose supplied to upstand or sink waste connection

Detergent

- Note that detergent is hazardous – read instructions and handle with care
- Insert hose into container of commercial dishwasher low foam detergent
- Detergent will come up to strength with use during the day

Rinse Fluid

- Insert hose into adjacent container of commercial dishwasher rinse fluid

Operation


- Run several cycles, ensure that operator has read and understands instructions

Troubleshooting Installation

- If machine doesn't fill after switching on power, check & ensure that hot water supply tap is open, water supply pressure is not below specification.


GLV Installation Diagram

GLV-S INST 23-06-16 3



All dimensions in millimeters

GLV Machine Operation



START UP

Turn machine on at wall. Fit filter, upstand and shut door.
Turn on power at the wall and press Power button on machine.
Power button light glows red and machine fills automatically
Wash and Rinse temperatures will begin to rise on the temperature gauges once the machine has filled.

OPERATION

Load rack into machine and shut door
Select either cycle 1 (60 seconds) or cycle 2 (150 seconds)
Cycle lights glow green while machine operates.
When Cycle lights go out, cycle is complete.

NOTE 1: Machine might operate longer than specified above if rinse water temperature is below required temperature.

SHUT DOWN EVERY NIGHT

Open door and press Drain button
Drain button glows blue as machine drains.
After draining starts remove drain upstand once the water level is below the top of the upstand.
Allow to drain for approximately 1 minute.
Turn Drain and Power buttons off.
Remove filter and rinse clean.
Replace filter and drain upstand.

DAILY CLEANING

The machine must be drained and cleaned at the end of each day.
Drain the machine as per the shut down instructions.
Remove, clean and replace filters.
Regularly check the wash and rinse jets and clean if necessary.

MAINTENANCE

Regular servicing of the dishwasher is essential for high performance, efficient operation and long machine life.
Contact us for information on a maintenance program.



STARLINE®

Service 0800 782 754
Parts 09 829 0930

Operating Procedures

PRE-RINSING

Pre-scraping of dishes is required by Food Hygiene Regulations. The best method is to pre-rinse with warm water with a Fisher Pre-rinse Unit – or alternatively by scraping or dunking in water. Cutlery should be pre-soaked in warm water, preferably containing cutlery pre-soak compound – refer your chemical supplier.

RACKING PROCEDURES

Do not overload racks or cutlery containers, minimise the overlap of crockery. Wash cutlery unsorted, handles down. Cycle times are short and water consumption per cycle low – so there is no advantage in overloading racks.

CYCLE TIMES

The GLV has 60 and 150 second cycles.

CHEMICAL

Correct type and quantity of detergent is essential for good results. Use good quality chemicals and regularly check containers. Discuss the use of drying agent and cutlery pre soak solution with your chemical supplier. Chemical concentrations can be adjusted by removing the front panel to gain access to the pumps. Detergent concentration can be increased by turning the adjusting screw clockwise. Rinse Fluid is set to a low injection rate and will take many cycles to prime. The operator can increase this by turning the adjusting screw anti-clockwise.


DRYING

Single tank commercial dishwashers do not have a drying cycle. However, the machines do rinse at high temperatures which promotes fast drying particularly when drying agents are used. At the end of the cycle promptly remove the rack from the machine – leave the rack on the bench for 2 to 3 minutes before emptying.

REGULAR CLEANING – at least once a week

Remove wash and rinse arms (1) by undoing the central thumbscrews (2). Inspect all jets – use toothpick or paperclip and remove arm end-caps if necessary to flush and clear.

Remove upstand (3), scrap trays (4, 5, 6) and filter (7). Clean and then replace all items.




Troubleshooting




Fault	Cause	Remedy
Filling		
Not filling	Water supply valve shut	Check Water supply valve
Filling during wash cycle	Door Switch not operating	Check Door is closed
	Upstand not fitted properly	Check Drain upstand is fitted
Heating		
Dishes not hot enough	Machine not rinsing	Check water supply temperature
	Rinsing but not hot	Check water supply temperature & arms spinning freely
Cycle start		
Does not start	Door switch	Check door is closed
Cycle Finish		
Wash too long	Water supply cold	Check water supply temperature
Performance		
Poor wash result	Detergent not used	Use quality low foam product
	Overloading racks	Do not overload racks
	Not pre-rinsing	Use Fisher pre-rinse
	Wash arms not rotating	Remove and clean arms/check bushes
	Wash jets blocked	Remove arms and clean jets
	Excessive soiling	Pre-rinse/use long cycle
Poor rinse results	Unrealistic expectation	E.g. baked on soiling requires pre-soaking
	Rinse jets blocked	Remove arms and clean jets
	Rinse arms not turning	Remove arms, clean jets, check bushes
	Poor racking procedures	Do not overload racks
Not drying	Excessive wash tank soil build up	Pre-rinse, change wash water regularly
	Poor wash/rinse performance	Refer above
	Low temperatures	Check heating systems
Foaming Wash	Drying agent not used	Use quality drying agent/rinse fluid
	Excessive Rinse Fluid	Adjust Rinse Fluid Injector

GLV7 Schematic Diagram

030172 05/04/16 1 A



Accessories

	Code	Description
	600 70080	Cuprack 450mm
	600 70081	Dishrack 450mm
	C660503	G Cutlery Container

Information supplied in this manual is copyright.
No part of this work may be reproduced or copied
in any form or by any means, electronic or
mechanical without the express permission of the
author/publisher

Manufactured in New Zealand by Washtech Ltd.

WASHTECH®

414 Rosebank Road
Avondale
Auckland 1026
New Zealand

PO Box 90548, Auckland

24HR Service 0800 Starline

Tel 09 829 0930

Fax 09 829 0935

E-mail info@washtech.co.nz

web www.starline.co.nz

ISO9001

All Washtech products are designed and
manufactured by Washtech using the
internationally recognised ISO9001 quality
management system, covering design,
manufacture and final inspection, ensuring
consistent high quality at all times.

In line with policy to continually develop and
improve its products, Washtech Ltd reserves the
right to change specifications and design without
prior notice.

